

KL

Wrap on Guide with
Stainless Steel




KL型ガイド

Single-foot design for spinning rod.
By adopting tangle free K-Frame, it releases line tangling automatically.

Kシリーズのシングルフットガイド。スピニング用。
キャスト絡みを激減させる糸絡み自動解除フレーム

Size Chart

| Ring Size | H mm | L1 mm | L mm |
|-----------|------|-------|------|
| 12 | 19.7 | 12.2 | 23.6 |
| 16 | 26.2 | 14.0 | 28.3 |
| 20 | 33.5 | 16.0 | 35.0 |
| 25 | 44.0 | 19.0 | 42.9 |
| 30 | 60.5 | 20.5 | 53.8 |



| | PKLSG | | GMKLSG | | KLSG | | EKLSG | | IGKLSG | | ICKLSG | |
|--------------------------|-----------------------|---|------------|--|----------|--|---------|--|-----------|---|-----------------|---|
| Frame Color | Polished Silver-White | | Shiny Gray | | Gunsmoke | | E Color | | I.P. Gold | | I.P. Shiny Gray | |
| Ring Material | SiC | | SiC | | SiC | | SiC | | SiC | | SiC | |
| Ring Type→ Ring Size↓ | S | J | S | | J | | J | | S | J | J | |
| 12 | | | | | | | | | | | | — |
| 16 | | | | | | | | | | | | — |
| 20 | | | | | | | | | | | | — |
| 25 | | | | | | | | | | | | — |
| 30 | | | | | | | | | | | | — |

● Deep Pressed Frame
深絞りフレーム

Example
表記例

- PKLSG 12S • CCKLAG 12
- GMKLSG 12S • BCKLAG 12

| | CCKLAG | | BCKLAG | | BKLAG | | KLAG | |
|--------------------------|----------------------|--|-------------------|--|----------|--|--------------|----|
| Frame Color | Frosted Silver-White | | Frosted Dark-Gray | | Black | | Silver-White | |
| Ring Material | ALCONITE | | ALCONITE | | ALCONITE | | ALCONITE | |
| Ring Type→ Ring Size↓ | UJ | | UJ | | UJ | | UJ | |
| 12 | | | | | | | | 12 |
| 16 | | | | | | | | 16 |
| 20 | | | | | | | | 20 |
| 25 | | | | | | | | 25 |
| 30 | | | | | | | | 30 |